Safety Data Sheet

Issue Date: 01-Nov-2011

Revision Date: 02-Dec-2014

Version 1

1. IDENTIFICATION

Product Identifier

Product Name

STALLION WORKHORSE

Other means of identification

Product Code

50-6300, 50-6302, 50-6304

UN/ID No

UN3266

Recommended use of the chemical and restrictions on use

Recommended Use

Industrial strength stripper.

Details of the supplier of the safety data sheet

Supplier Address

Cleaning Ideas Corp.

P.O. Box 7269 San Antonio, TX 78207

Emergency Telephone Number

Company Phone Number Emergency Telephone (24 hr) Phone: 1-210-227-9161 Fax: 1-210-227-0002 INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance non viscous

Physical State Liquid

Odor Butyl odor

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category C
Serious eye damage/eye irritation	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word Danger

Hazard Statements

Harmful if swallowed Toxic if inhaled

Causes severe skin burns and eye damage



STALLION WORKHORSE Revision Date: Oct. 2, 2015

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a poison center or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a poison center or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a poison center or doctor/physician if you feel unwell

Immediately call a poison center or doctor/physician

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do not induce vomiting

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethylene Glycol Monobutyl Ether	111-76-2	30-50
Monoethanolamine	141-43-5	5-15
Trade Secret	Proprietary	5-10
Caustic Potash (KOH) Liq 45%	1310-58-3	<2

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get immediate medical attention.

Skin Contact Immediately flush thoroughly with water for at least 15 minutes. Remove contaminated

clothing and shoes. Wash contaminated clothing before reuse. Seek immediate medical

attention/advice.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen.

Ingestion Seek medical attention immediately. Call a poison control center or doctor immediately for

treatment advice. Have person sip a glass of water if able to swallow. Never give anything

by mouth to an unconscious person.

STALLION WORKHORSE Revision Date: Oct. 2, 2015

Most important symptoms and effects

Symptoms

Causes severe skin burns and eye damage.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

May aggravate pre-existing skin disorders. Prolonged skin contact may result in absorption of harmful amounts. Target organ effects: Liver and Kidney.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam, Dry chemical, Carbon dioxide (CO2).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Protective equipment and precautions for firefighters

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode or other positive pressure mode. Use personal protective equipment comprising suitable gloves, fire resistant boots, eye protection, and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Use personal protective equipment as required.

Methods and material for containment and cleaning up

Methods for Containment

Stop all leaks. Isolate area. Keep unnecessary and unprotected personnel from entering contaminated area. Absorb material with an inert material. Prevent from entering drains, sewers, or other bodies of water, absorb unrecoverable product. Transfer contaminated material to containers for disposal.

Methods for Clean-Up

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Wear protective gloves/protective clothing and eye/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep out of

the reach of children.

Incompatible Materials

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³	
Monoethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³	
Caustic Potash (KOH) Liq 45% 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³	

Appropriate engineering controls

Engineering Controls

Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Avoid contact with eyes.

Skin and Body Protection

Wear suitable protective clothing.

Respiratory Protection

Ensure adequate ventilation, especially in confined areas.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES Information on basic physical and chemical properties Physical State Liquid Appearance non viscous Odor Butyl odor Color According to product specification Odor Threshold Not determined

Remarks • Method

PropertyValuespHNot determinedMelting Point/Freezing PointNot determinedBoiling Point/Boiling RangeNot determinedFlash PointNot determined

Evaporation Rate Not determined Flammability (Solid, Gas) Not determined **Upper Flammability Limits** Not determined Lower Flammability Limit Not determined Vapor Pressure Not determined Vapor Density Not determined Specific Gravity Not determined Water Solubility Not determined Solubility in other solvents Not determined

Partition Coefficient
Auto-ignition Temperature
Decomposition Temperature
Kinematic Viscosity
Dynamic Viscosity
Explosive Properties

Not determined
Not determined
Not determined
Not determined
Not determined

Oxidizing Properties

Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact

Causes serious eye damage.

Skin Contact

Causes severe skin burns.

Inhalation

Toxic if inhaled.

Ingestion

Harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50		
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	(= 2.21 mg/L (Rat) 4 h = 450 pp (Rat) 4 h		
Monoethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg(Rabbit)= 1025 mg/kg (Rabbit)			
Trade Secret	= 1000 mg/kg(Rat)	-			
Trade Secret	= 10 g/kg (Rat)	-	-		
Caustic Potash (KOH) Liq 45% 1310-58-3	= 214 mg/kg (Rat)	-	-		
Trade Secret	= 1310 mg/kg (Rat)	= 2 mL/kg (Rabbit)			

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether 111-76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)
Group 3 IARC components are "not classifiable as human carcinogens"
STOT - repeated exposure Liver. Kidneys.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethylene Glycol Monobutyl Ether 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Monoethanolamine 141-43-5	15: 72 h Desmodesmus subspicatus mg/L EC50	227: 96 h Pimephales promelas mg/L LC50 flow-through 3684: 96 h Brachydanio rerio mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through		65: 48 h Daphnia magna mg/L EC50
Trade Secret	1.01: 72 h Desmodesmus subspicatus mg/L EC50	41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static		610: 24 h Daphnia magna mg/L EC50
Caustic Potash (KOH) Liq 45% 1310-58-3		80: 96 h Gambusia affinis mg/L LC50 static		15

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

STALLION WORKHORSE

 Chemical Name
 Partition Coefficient

 Ethylene Glycol Monobutyl Ether
 0.81

 111-76-2
 -1.91

 Monoethanolamine
 -1.91

 141-43-5
 -1.91

 Caustic Potash (KOH) Liq 45%
 0.83

 1310-58-3
 0.83

Revision Date: Oct. 2, 2015

Other Adverse Effects

Not determined.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Caustic Potash (KOH) Liq 45%	Toxic
1310-58-3	Corrosive

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN3266

Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s. (potassium hydroxide, ethanolamine)

Hazard Class 8
Packing Group III

UN/ID No Regulated UN3266

Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s. (potassium hydroxide, ethanolamine)

Hazard Class 8
Packing Group |||

IMDG Regulated UN/1D No UN3266

Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s. (potassium hydroxide, ethanolamine)

Hazard Class 8
Packing Group III

15. REGULATORY INFORMATION

1 4	1
International	Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethylene Glycol Monobutyl Ether	Present	X		Present		Present	Х	Present	Х	Х
Monoethanolamine	Present	X		Present		Present	Х	Present	Х	Х
Trade Secret	Present	X		Present		Present	Х	Present	Х	X
Caustic Potash (KOH) Liq 45%	Present	Х		Present		Present	Х	Present	Х	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Caustic Potash (KOH) Liq 45%	1000 lb		RQ 1000 lb final RQ
1310-58-3			RQ 454 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	30-50	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Caustic Potash (KOH) Liq 45%	1000 lb			X

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Monoethanolamine 141-43-5	X	Χ ·	Х
Caustic Potash (KOH) Liq 45% 1310-58-3	X	X	Х

STALLION WORKHORSE

Revision Date: Oct. 2, 2015

16. OTHER INFORMATION

NFPA

Health Hazards Not determined

Flammability
Not determined

Instability
Not determined
Physical Hazards

Special Hazards Not determined Personal Protection

HMIS

Health Hazards Not determined Flammability
Not determined

Physical Hazards Not determined

Not determined

Issue Date: Revision Date: Revision Note: 01-Nov-2011 02-Dec-2014 New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet